

# Ecronova® KDA 790

---

**BRAND FAMILY OVERVIEW** Ecronova® KDA styrene-acrylic polymer dispersions are ideally suited for architectural coatings on fresh construction materials as well as refurbished building surfaces. Specific grades are designed for paint, primer, and sealer applications. These versatile polymers feature high filler loading tolerance, exceptional penetration into mineral-based substrates, and excellent water and alkali resistance.

**USAGE** This APE free emulsion imparts water vapor permeability, weather-ability and UV light stability and is suitable for low VOC interior paints and silicate exterior paints.

**DESCRIPTION** Water-based styrene-acrylic copolymer emulsion

**PERFORMANCE ATTRIBUTES** This product is used in many applications including the following:

Market	Properties Imparted
Building Paints	water resistance, weatherability

**PHYSICAL PROPERTIES** The following properties are typical but should not be considered specifications:

Appearance:	white liquid
Solids Type:	Styrene/Acrylic copolymer
Emulsifier Charge:	Anionic
Minimum Film Forming Temperature (degrees Celsius) :	0
Non-Volatile (%) :	49.0 - 51.0
pH:	7.0 - 9.0
Brookfield Viscosity (cps) :	50 - 800
Spindle Number:	2
RPM:	20
Shelf Life (months) :	The product has a shelf life of 12 months from date of manufacture when storage and handling instructions are followed.

**SITE OF MANUFACTURE (and PRODUCT CODE)** Recklinghausen (ECKD790.R)

# Ecronova® KDA 790

---

---

**APPLICATION DATA** This emulsion is compatible with most common additives, pigments and pigment preparations and can be combined with other emulsions. Due to the variety of products in the market, compatibility and storage stability have to be tested from case to case. Polyurethane thickeners are highly recommended but most commercial thickeners can be used. Due to the low minimum film forming temperature of this emulsion it is not mandatory to add coalescing agents. For application properties of the final product it might be helpful to add co-solvents like butyl glycol, butyl diglycol, Texanol or glycoether. For Storage and Safety information see Material Safety Data Sheet.

---

**STORAGE** Keep containers tightly closed in a dry, cool and well-ventilated place. Keep from freezing.

---

**HANDLING** Ensure adequate ventilation. Handle in accordance with good industrial hygiene and safety practice. Use personal protective equipment as required.

---

Revised 09 April 2018

The following information for this product, specific to each site of manufacture, is available upon request:

- Material Safety Data Sheets in various formats and languages (includes global chemical inventory listing)
- Food Contact Declaration of Compliance (if applicable)

# Ecronova® KDA 790

---

## Americas

Michelman Inc.  
9080 Shell Road  
Cincinnati, Ohio 45236-1299 USA  
Tel: +1 513 793 7766  
Fax: +1 513 793 2504

## Asia Pacific

Michelman Asia-Pacific Pte. Ltd.  
2A Tuas Avenue 12  
Singapore 639023  
Tel: +65 6861 2822  
Fax: +65 6861 2262

## Europe, Middle East, Africa

Michelman SARL  
11, rue de l'Industrie  
L-8399 Windhof  
Luxembourg  
Tel: +352 26 39 44 1  
Fax: +352 26 39 44 80

## China

Michelman (Shanghai)  
Chemical Trading Co., Ltd.  
Room 127, Building 5  
Zhongtian Science Technology Park  
No. 787 Kangqiao Road  
Shanghai, China 201315  
Tel: +86 21 2098 6880  
Fax: +86 21 2098 6881

## India

Michelman Private Limited  
(formerly known as  
Michelman Chemicals Pvt Ltd)  
First Floor  
Plot NO 61CD  
Government Industrial Estate  
Charkop, Kandivali (West)  
Mumbai-400 067  
India  
Tel: +91 22 28672783  
Fax: +91 22 28672784

The facts stated and the recommendations contained herein are based on our own research and the research of others, and are believed to be accurate. However, no guarantee of their accuracy is made because we cannot cover every possible application for our products nor anticipate every variation encountered in manufacturing equipment and methods. The products discussed are sold without warranty, express or implied and Seller disclaims any warranty of merchantability or fitness for a particular purpose in connection with the purchase of its products. It is recommended that purchasers conduct their own tests to determine the suitability of such products for their particular purpose. Seller shall not be liable for any injury, loss or damage, direct or consequential arising out of the use of or the inability to use the product. Statements concerning the possible use of our products are not intended as recommendations to use our products in the infringement of any patent and our products are sold without warranty of non-infringement.

© 2018 MICHELMAN, INC. All rights reserved. ® Reg. U.S. Pat. TM Off.  
All marks contained herein are registered or owned by Michelman, Inc.  
Michelman is ISO 9001:2015 certified.