MICHELMAN

Licomer® M 55

BRAND FAMILY OVERVIEW	Licomer [®] is a family of water-based polymer dispersions and wax emulsions for the manufacture of dry-bright emulsions intended for floor polish, automotive polish, shoe polish and leather polish applications.	
USAGE	Designed for the manufacture of dry-bright emulsions intended especially for the care of floors. This product provides high gloss, good traffic resistance, good dirt repellence and low presence of black heel marks, easy removal with ammonium cleaning agents, and excellent water and detergent resistance.	
DESCRIPTION	Styrene- Acrylate copolymer polymer dispersion	
PERFORMANCE ATTRIBUTES	This product is used in many applications including the following:	
	Market	Properties Imparted
	Household	detergent resistance for Polishes, dirt pick-up resistance, dry bright, hardness, water resistance
	Industrial & Institutional	black heel resistance, buffability, detergent resistance for Polishes, dirt pick-up resistance, dry bright, easy removal, traffic resistance, water resistance
PHYSICAL PROPERTIES	The following properties are typical but should not b	e considered specifications:
	Appearance:	milky white liquid
	Solids Type:	Styrene/Acrylic copolymer
	Emulsifier Charge:	Anionic / Nonionic
	Minimum Film Forming Temperature (degrees Celsius) :	55
	Non-Volatile (%) :	37.0 - 39.0
	pH:	8.0 - 9.5
	Brookfield Viscosity (cps) :	0 - 140
	Shelf Life (months) :	The product has a shelf life of 18 months from date of manufacture when storage and handling instructions are followed.
STORAGE	Keep containers tightly closed in a dry freezing.	v, cool and well-ventilated place. Keep from

MICHELMAN

Licomer® M 55

HANDLING Avoid contact with eyes, skin and clothing. Ensure adequate ventilation. Handle in accordance with good industrial hygiene and safety practice.

Revised 03 August 2020

The following information for this product, specific to each site of manufacture, is available upon request:

- Material Safety Data Sheets in various formats and languages (includes global chemical inventory listing)
- Food Contact Declaration of Compliance (if applicable)

Americas Luxembourg Singapore Michelman Inc. Michelman International SARL Michelman Asia-Pacific Pte. Ltd. Tel: +1 513 793 7766 Tel: +352 26 39 44 1 Tel: +65 6861 2822 Fax: +1 513 793 2504 Fax: +352 26 39 44 80 Fax: +65 6861 2262 China India Michelman New Material Michelman Private Limited (Shanghai) Co., Ltd. Tel: +91 22 6221 3800 Tel: +86 21 3810 3800 Fax: +91 22 6221 3801/02 Fax: +86 21 3810 3811

The facts stated and the recommendations contained herein are based on our own research and the research of others, and are believed to be accurate. However, no guarantee of their accuracy is made because we cannot cover every possible application for our products nor anticipate every variation encountered in manufacturing equipment and methods. The products discussed are sold without warranty, express or implied and Seller disclaims any warranty of merchantability or fitness for a particular purpose in connection with the purchase of its products. It is recommended that purchasers conduct their own tests to determine the suitability of such products for their particular purpose. Seller shall not be liable for any injury, loss or damage, direct or consequential arising out of the use of or the inability to use the product. Statements concerning the possible use of our products are not intended as recommendations to use our products in the infringement of any patent and our products are sold without warranty of non-infringement.

© 2024 MICHELMAN, INC. All rights reserved. ® Reg. U.S. Pat. TM Off. All marks contained herein are registered or owned by Michelman, Inc. Michelman is ISO 9001:2015 certified.