

Michem® Emulsion 48040M2

BRAND FAMILY OVERVIEW Michem® Emulsion is a versatile family of products that adds value to a wide range of markets. These markets include paint & coatings, fiberglass, inks & OPVs, floor care, wood finishes, automotive care products, building products, carpets, die lubricants, textiles and urethane foam.

USAGE This water-based emulsion provides excellent anti-blocking and release properties for building paint, and industrial molding and wood applications.

DESCRIPTION Microcrystalline wax emulsion

PERFORMANCE ATTRIBUTES This product is used in many applications including the following:

This product is used in many applications including the following.	
Market	Properties Imparted
Building Paints	block resistance, release
Die Lubes & Mold Releases	mold release
Exterior Wood Protection	release
Inks	block resistance, release
Interior Furniture & Floor	release
OEM Applied Wood Protection	block resistance, lubricity
Overprint Varnishes	block resistance, release
Technical Textiles	adhesion promotion
Urethane Foam	release

PHYSICAL PROPERTIES The following properties are typical but should not be considered specifications: Off-white, opaque liquid Appearance: Solids Type: Microcrystalline Wax Freeze/Thaw Stability: None: protect from freezing Non-Volatile (%): 39.5 - 40.5 Specific Gravity: 0.96 - 0.98< 10.0 Recommended pH of your system: 1.0 - 12.0 Brookfield Viscosity (cps): < 200 2 Spindle Number: RPM: 60

(and PRODUCT CODE)

SITE OF MANUFACTURE USA (ME48040M2)

page 1 www.michelman.com



Michem® Emulsion 48040M2

STORAGE Keep container tightly closed. Keep containers tightly closed in a dry, cool and well-ventilated place. Keep from freezing.

HANDLING Ensure adequate ventilation. Handle in accordance with good industrial hygiene and safety practice. Use personal protective equipment as required.

Revised 03 August 2020

The following information for this product, specific to each site of manufacture, is available upon request:

- Material Safety Data Sheets in various formats and languages (includes global chemical inventory listing)
- Food Contact Declaration of Compliance (if applicable)

Americas

Michelman Inc. Tel: +1 513 793 7766 Fax: +1 513 793 2504

Michelman New Material (Shanghai) Co., Ltd. Tel: +86 21 3810 3800 Fax: +86 21 3810 3811

warranty of non-infringement.

Luxembourg

Michelman International SARL Tel: +352 26 39 44 1 Fax: +352 26 39 44 80

Michelman Private Limited Tel: +91 22 6221 3800 Fax: +91 22 6221 3801/02

use of or the inability to use the product. Statements concerning the possible use of our products are not intended as recommendations to use our products in the infringement of any patent and our products are sold without

Singapore

Michelman Asia-Pacific Pte. Ltd. Tel: +65 6861 2822 Fax: +65 6861 2262

The facts stated and the recommendations contained herein are based on our own research and the research of others, and are believed to be accurate. However, no guarantee of their accuracy is made because we cannot cover every possible application for our products nor anticipate every variation encountered in manufacturing equipment and methods. The products discussed are sold without warranty, express or implied and Seller disclaims any warranty of merchantability or fitness for a particular purpose in connection with the purchase of its products. It is recommended that purchasers conduct their own tests to determine the suitability of such products for their particular purpose. Seller shall not be liable for any injury, loss or damage, direct or consequential arising out of the

© 2024 MICHELMAN, INC. All rights reserved. ® Reg. U.S. Pat. TM Off. All marks contained herein are registered or owned by Michelman, Inc. Michelman is ISO 9001:2015 certified

page 2 www.michelman.com