MICHELMAN[®]

Michem® Emulsion 62330

BRAND FAMILY OVERVIEW	Michem® Emulsion is a versatile family of products that adds value to a wide range of markets. These markets include paint & coatings, fiberglass, inks & OPVs, floor care, wood finishes, automotive care products, building products, carpets, die lubricants, textiles and urethane foam.		
USAGE	This fine particle-sized emulsion provides excellent water repellency, corrosion resistance, block resistance, and lubricity when added to varnishes and other coatings without gloss degradation.		
DESCRIPTION	Paraffin / polyethylene wax blend emulsion		
PERFORMANCE ATTRIBUTES	This product is used in many applications including the following:		
	Market	Properties Imparted	
	Concrete	water beading, water resistance	
	Exterior Wood Protection	block resistance, water beading, water resistance	
	Interior Furniture & Floor	water resistance	
	OEM Applied Wood Protection	water resistance	
	Overprint Varnishes	block resistance, water beading, water resistance	
PHYSICAL PROPERTIES	The following properties are typical but should not be considered specifications:		
	Appearance:	Amber, translucent liquid	
	Solids Type:	Paraffin / Polyethylene Wax blend	
	Freeze/Thaw Stability:	None: protect from freezing	
	Non-Volatile (%) :	29.5 - 30.5	
	Specific Gravity:	0.97 - 0.99	
	pH:	9.4 - 10.4	
	Recommended pH of your system:	> 7.0	
	Brookfield Viscosity (cps) :	50 max	
	Spindle Number:	1	
	RPM:	60	

SITE OF MANUFACTURE USA (ME62330), Belgium (ME62330.E), Singapore (ME62330.S)

MICHELMAN

Michem® Emulsion 62330

STORAGE	Keep containers tightly closed in a dry, cool and well-ventilated place. Keep from freezing.						
HANDLING	Handle in accordance with good industrial hygiene and safety practice. Use personal protection equipment.						
	Revised 13 September 2022						
	The following information for this product, specific to each site of manufacture, is available upon request: • Material Safety Data Sheets in various formats and languages (includes global chemical inventory listing) • Food Contact Declaration of Compliance (if applicable)						
					Americas	Luxembourg	Singapore
					Michelman Inc.	Michelman International SARL	Michelman Asia-Pacific Pte. Ltd.
	Tel: +1 513 793 7766	Tel: +352 26 39 44 1	Tel: +65 6861 2822				
		Fax: +1 513 793 2504	Fax: +352 26 39 44 80	Fax: +65 6861 2262			
		China	India				
	Michelman New Material	Michelman Private Limited					

Tel: +91 22 6221 3800

Fax: +91 22 6221 3801/02

Michelman New Material (Shanghai) Co., Ltd. Tel: +86 21 3810 3800 Fax: +86 21 3810 3811

The facts stated and the recommendations contained herein are based on our own research and the research of others, and are believed to be accurate. However, no guarantee of their accuracy is made because we cannot cover every possible application for our products nor anticipate every variation encountered in manufacturing equipment and methods. The products discussed are sold without warranty, express or implied and Seller disclaims any warranty of merchantability or fitness for a particular purpose in connection with the purchase of its products. It is recommended that purchasers conduct their own tests to determine the suitability of such products for their particular purpose. Seller shall not be liable for any injury, loss or damage, direct or consequential arising out of the use of or the inability to use the product. Statements concerning the possible use of our products are not intended as recommendations to use our products in the infringement of any patent and our products are sold without warranty of non-infringement.

© 2025 MICHELMAN, INC. All rights reserved. [®] Reg. U.S. Pat. TM Off. All marks contained herein are registered or owned by Michelman, Inc. Michelman is ISO 9001:2015 certified.