MICHELMAN

Michem® Lube 693

BRAND FAMILY OVERVIEW	Michem [®] Lube is a versatile family of nanoscale wax emulsions, which are mostly carnauba and paraffin-based, used to improve processing and performance in many industries, as well as provide a wide array of surface properties.	
USAGE	This emulsion enhances water repellency, water bead, moisture, and vapor resistance in wood coating applications.	
DESCRIPTION	Polyethylene / Paraffin Wax blend Emulsion	
PERFORMANCE ATTRIBUTES	This product is used in many applications including the following:	
	Market	Properties Imparted
	Exterior Wood Protection	release, water beading, water repellence, water resistance
	Inks	water repellence
	OEM Applied Wood Protection	water resistance
	Overprint Varnishes	water repellence
	Technical Textiles	lubricity
PHYSICAL PROPERTIES	The following properties are typical but should not be considered specifications:	
	Appearance:	Cream colored liquid
	Freeze/Thaw Stability:	None: protect from freezing
	Non-Volatile (%) :	38.5 - 39.5
	Specific Gravity:	0.96 - 0.98
	pH:	9.0 - 10.0
	Recommended pH of your system:	> 7.0
	Brookfield Viscosity (cps) :	100 - 750
	Spindle Number:	3
	RPM:	60
	Shelf Life (months) :	The product has a shelf life of 12 months from date of manufacture when storage and handling instructions are followed.
SITE OF MANUFACTURE (and PRODUCT CODE)	USA (ML693)	
STORAGE	Keep containers tightly closed in a d	y, cool and well-ventilated place. Keep from

STORAGE Keep containers tightly closed in a dry, cool and well-ventilated place. Keep from freezing.

MICHELMAN

Michem® Lube 693

HANDLING Handle in accordance with good industrial hygiene and safety practice. Use personal protective equipment as required.

Revised 04 August 2020

The following information for this product, specific to each site of manufacture, is available upon request:

- Material Safety Data Sheets in various formats and languages (includes global chemical inventory listing)
- Food Contact Declaration of Compliance (if applicable)

Americas Luxembourg Michelman Inc. Michelman International SARL Tel: +1 513 793 7766 Tel: +352 26 39 44 1 Fax: +1 513 793 2504 Fax: +352 26 39 44 80

Michelman New Material (Shanghai) Co., Ltd. Tel: +86 21 3810 3800 Fax: +86 21 3810 3811

China

India Michelman Private Limited Tel: +91 22 6221 3800 Fax: +91 22 6221 3801/02 Singapore

Michelman Asia-Pacific Pte. Ltd. Tel: +65 6861 2822 Fax: +65 6861 2262

The facts stated and the recommendations contained herein are based on our own research and the research of others, and are believed to be accurate. However, no guarantee of their accuracy is made because we cannot cover every possible application for our products nor anticipate every variation encountered in manufacturing equipment and methods. The products discussed are sold without warranty, express or implied and Seller disclaims any warranty of merchantability or fitness for a particular purpose in connection with the purchase of its products. It is recommended that purchasers conduct their own tests to determine the suitability of such products for their particular purpose. Seller shall not be liable for any injury, loss or damage, direct or consequential arising out of the use of or the inability to use the product. Statements concerning the possible use of our products are not intended as recommendations to use our products in the infringement of any patent and our products are sold without warranty of non-infringement.

© 2024 MICHELMAN, INC. All rights reserved. ® Reg. U.S. Pat. TM Off. All marks contained herein are registered or owned by Michelman, Inc. Michelman is ISO 9001:2015 certified.