

Michem® Dispersion Urethane 2012B

BRAND FAMILY OVERVIEW Michem® Dispersion Urethanes are water-based polyurethane dispersions that can enhance toughness, scratch resistance, water resistance and flexibility of coatings. Michem Dispersion Urethanes are useful for industrial wood, concrete, and metal substrates.

USAGE Provides abrasion, water, and blocking resistance and fast hardness development for floor coatings, parquet lacquers, and industrial coatings.

DESCRIPTION Water-based polyurethane-acrylic hybrid system

	Market	Properties Imparted
	Concrete	abrasion resistance, block resistance, chemical resistance, hardness, water resistance
	OEM Applied Wood Protection	abrasion resistance, block resistance, chemical resistance, hardness, water resistance
	On-Site Applied Wood Protection	abrasion resistance, block resistance, chemical resistance, hardness, water resistance

PHYSICAL PROPERTIES

Appearance:	White liquid	
Solids Type:	Polyurethane Acrylic hybrid	
Emulsifier Charge:	Anionic	
Minimum Film Forming Temperature (degrees Celsius):	30	
Non-Volatile (%) :	34.0 - 36.0	
pH:	7.0 - 9.0	
Brookfield Viscosity (cps):	10 - 300	
Spindle Number:	2	
RPM:	20	
Shelf Life (months) :	The product has a shelf life of 12 months from date of manufacture when storage and handling instructions are followed.	

page 1 www.michelman.com



Michem® Dispersion Urethane 2012B

APPLICATION DATA This dispersion is compatible with most common additives, pigments, and pigment preparations and can be combined with other emulsions. Due to the variety of products in the market, compatibility and storage stability have to be tested from case to case. Polyurethane thickeners can be used. Due to the minimum film forming temperature of this dispersion it is mandatory to add coalescing agents.

STORAGE Keep containers tightly closed in a dry, cool and well-ventilated place. Keep from freezing.

HANDLING Ensure adequate ventilation. Handle in accordance with good industrial hygiene and safety practice.

Revised 07 December 2021

The following information for this product, specific to each site of manufacture, is available upon request:

- Material Safety Data Sheets in various formats and languages (includes global chemical inventory listing)
- Food Contact Declaration of Compliance (if applicable)

Americas

Michelman Inc. Tel: +1 513 793 7766 Fax: +1 513 793 2504

China

Michelman New Material (Shanghai) Co., Ltd. Tel: +86 21 3810 3800 Fax: +86 21 3810 3811

Luxembourg

Michelman International SARL Tel: +352 26 39 44 1 Fax: +352 26 39 44 80

Michelman Private Limited Tel: +91 22 6221 3800 Fax: +91 22 6221 3801/02

Singapore

Michelman Asia-Pacific Pte. Ltd. Tel: +65 6861 2822 Fax: +65 6861 2262

The facts stated and the recommendations contained herein are based on our own research and the research of others, and are believed to be accurate. However, no guarantee of their accuracy is made because we cannot cover every possible application for our products nor anticipate every variation encountered in manufacturing equipment and methods. The products discussed are sold without warranty, express or implied and Seller disclaims any warranty of merchantability or fitness for a particular purpose in connection with the purchase of its products. It is recommended that purchasers conduct their own tests to determine the suitability of such products for their particular purpose. Seller shall not be liable for any injury, loss or damage, direct or consequential arising out of the use of or the inability to use the product. Statements concerning the possible use of our products are not intended as recommendations to use our products in the infringement of any patent and our products are sold without warranty of non-infringement.

© 2024 MICHELMAN, INC. All rights reserved. ® Reg. U.S. Pat. TM Off. All marks contained herein are registered or owned by Michelman, Inc. Michelman is ISO 9001:2015 certified

page 2 www.michelman.com