

Wax Dispersion 40

BRAND FAMILY OVERVIEW Wax Dispersion products are solventborne and enhance water resistance and slip/release. Applications normally include decks, architectural coatings, and industrial coatings.

USAGE Most effective as a water repellent aid, this dispersion also has some slip and release properties in solvent applications. It is most effective when used in formulations for deck, architectural and industrial coatings.

DESCRIPTION Solvent dispersion of paraffin wax

PERFORMANCE ATTRIBUTES This product is used in many applications including the following:

| Market | Properties Imparted |
|--------------------------|--|
| Automotive Care | <i>buffability</i> |
| Exterior Wood Protection | <i>water beading, water repellence, water resistance</i> |

PHYSICAL PROPERTIES The following properties are typical but should not be considered specifications:

| | |
|------------------------------|--------------|
| Appearance: | Opaque paste |
| Solids Type: | Paraffin |
| Non-Volatile (%) : | 39.5 - 40.5 |
| Brookfield Viscosity (cps) : | paste |

SITE OF MANUFACTURE (and PRODUCT CODE) USA (WD40)

STORAGE Keep away from open flames, hot surfaces and sources of ignition. Keep container tightly closed. Keep from freezing. Keep in properly labeled containers. Keep tightly closed in a dry and cool place.

HANDLING Avoid contact with eyes, skin and clothing. Ensure adequate ventilation. Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharges. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded. Use only in an area containing flame proof equipment. Use personal protective equipment as required.

Wax Dispersion 40

Revised 06 December 2014

The following information for this product, specific to each site of manufacture, is available upon request:

- Material Safety Data Sheets in various formats and languages (includes global chemical inventory listing)
- Food Contact Declaration of Compliance (if applicable)

Americas

Michelman Inc.
Tel: +1 513 793 7766
Fax: +1 513 793 2504

China

Michelman New Material
(Shanghai) Co., Ltd.
Tel: +86 21 2098 6880
Fax: +86 21 3810 3811

India

Michelman Private Limited
(formerly known as
Michelman Chemicals Pvt Ltd)
Tel: +91 22 28672783
Fax: +91 22 28672784

Japan

Michelman Japan LLC
Tel: +81 3 45 80 14 90
Fax: +81 3 45 80 27 01

Luxembourg

Michelman SARL
Tel: +352 26 39 44 1
Fax: +352 26 39 44 80

Singapore

Michelman Asia-Pacific Pte. Ltd.
Tel: +65 6861 2822
Fax: +65 6861 2262

The facts stated and the recommendations contained herein are based on our own research and the research of others, and are believed to be accurate. However, no guarantee of their accuracy is made because we cannot cover every possible application for our products nor anticipate every variation encountered in manufacturing equipment and methods. The products discussed are sold without warranty, express or implied and Seller disclaims any warranty of merchantability or fitness for a particular purpose in connection with the purchase of its products. It is recommended that purchasers conduct their own tests to determine the suitability of such products for their particular purpose. Seller shall not be liable for any injury, loss or damage, direct or consequential arising out of the use of or the inability to use the product. Statements concerning the possible use of our products are not intended as recommendations to use our products in the infringement of any patent and our products are sold without warranty of non-infringement.

© 2019 MICHELMAN, INC. All rights reserved. ® Reg. U.S. Pat. TM Off.
All marks contained herein are registered or owned by Michelman, Inc.
Michelman is ISO 9001:2015 certified.