

Hydraban® 8000

BRAND FAMILY OVERVIEW Water-based Hydraban® paper treatments offer water repellency with excellent gluability and printability. Hydraban® penetrates into the paper, giving a wax impregnated look to the finished sheet without sacrificing recyclability.

USAGE A water-based treatment for kraft paper that imparts a high degree of water repellency, and is printable and gluable. It can be applied at the wet end or dry end of the corrugator, or with an off-line treating operation. Also certified by Biodegradable Products Institute (BPI) as compostable, Hydraban® 8000 has a usage limit of 8% by dry weight of the final article for compostability.

DESCRIPTION Repulpable water resistant paper coating.

PERFORMANCE ATTRIBUTES This product is used in many applications including the following:

Market	Properties Imparted
Perishables	<i>water resistance</i>

PHYSICAL PROPERTIES The following properties are typical but should not be considered specifications:

Appearance:	White liquid
Solids Type:	Proprietary
EZ Cup Viscosity (sec) :	8 - 12
Cup Number:	3
pH:	10.0 - 11.0
Brookfield Viscosity (cps) :	0 - 600
Spindle Number:	3
RPM:	60
Shelf Life (months) :	The product has a shelf life of 12 months from date of manufacture when storage and handling instructions are followed.

SITE OF MANUFACTURE (and PRODUCT CODE) USA (HY8000)

APPLICATION DATA Hydraban® 8000 may be applied at the corrugator by blade or rod and may also be spray applied.

STORAGE Keep containers tightly closed in a dry, cool and well-ventilated place. Keep from freezing.

Hydraban® 8000

HANDLING Ensure adequate ventilation. Handle in accordance with good industrial hygiene and safety practice.

Revised 05 August 2021

The following information for this product, specific to each site of manufacture, is available upon request:

- Material Safety Data Sheets in various formats and languages (includes global chemical inventory listing)
- Food Contact Declaration of Compliance (if applicable)

Americas

Michelman Inc.
Tel: +1 513 793 7766
Fax: +1 513 793 2504

China

Michelman New Material
(Shanghai) Co., Ltd.
Tel: +86 21 2098 6880
Fax: +86 21 3810 3811

India

Michelman Private Limited
Tel: +91 22 28672783
Fax: +91 22 28672784

Japan

Michelman Japan LLC
Tel: +81 3 45 80 14 90
Fax: +81 3 45 80 27 01

Luxembourg

Michelman International SARL
Tel: +352 26 39 44 1
Fax: +352 26 39 44 80

Singapore

Michelman Asia-Pacific Pte. Ltd.
Tel: +65 6861 2822
Fax: +65 6861 2262

The facts stated and the recommendations contained herein are based on our own research and the research of others, and are believed to be accurate. However, no guarantee of their accuracy is made because we cannot cover every possible application for our products nor anticipate every variation encountered in manufacturing equipment and methods. The products discussed are sold without warranty, express or implied and Seller disclaims any warranty of merchantability or fitness for a particular purpose in connection with the purchase of its products. It is recommended that purchasers conduct their own tests to determine the suitability of such products for their particular purpose. Seller shall not be liable for any injury, loss or damage, direct or consequential arising out of the use of or the inability to use the product. Statements concerning the possible use of our products are not intended as recommendations to use our products in the infringement of any patent and our products are sold without warranty of non-infringement.

© 2022 MICHELMAN, INC. All rights reserved. ® Reg. U.S. Pat. TM Off.
All marks contained herein are registered or owned by Michelman, Inc.
Michelman is ISO 9001:2015 certified.