MICHELMAN

Michem® Emulsion 20117

BRAND FAMILY OVERVIEW	Michem [®] Emulsion is a versatile family of products that adds value to a wide range of markets. These markets include paint & coatings, fiberglass, inks & OPVs, floor care, wood finishes, automotive care products, building products, carpets, die lubricants, textiles and urethane foam.	
USAGE	This additive provides slip and anti-block properties in auto polish formulations.	
DESCRIPTION	Cationic carnauba emulsion	
PERFORMANCE ATTRIBUTES	This product is used in many applications including the following:	
	Market	Properties Imparted
	Automotive Care	adhesion, APEO free, buffability, gloss enhancement, lubricity, mar resistance
PHYSICAL PROPERTIES	The following properties are typical but should not be considered specifications:	
	Appearance:	Black, translucent liquid
	Solids Type:	Carnauba
	Freeze/Thaw Stability:	None: protect from freezing
	Non-Volatile (%) :	16.0 - 18.0
	Specific Gravity:	0.99 - 1.01
	pH:	4.5 - 6.5
	Recommended pH of your system:	< 7.0
	Brookfield Viscosity (cps) :	< 50
	Spindle Number:	1
	RPM:	60
SITE OF MANUFACTURE (and PRODUCT CODE)	USA (ME20117)	
STORAGE		y, cool and well-ventilated place. Keep from ildren. Protect from moisture. Store away o.

MICHELMAN[®]

Michem® Emulsion 20117

HANDLING Avoid contact with skin, eyes or clothing. Do not eat, drink or smoke when using this product. Handle in accordance with good industrial hygiene and safety practice. Handle product only in closed system or provide appropriate exhaust ventilation. In case of insufficient ventilation, wear suitable respiratory equipment. Take off contaminated clothing and wash before reuse. Use personal protection equipment.

Revised 06 September 2022

The following information for this product, specific to each site of manufacture, is available upon request: • Material Safety Data Sheets in various formats and languages (includes global chemical inventory listing)

• Food Contact Declaration of Compliance (if applicable)

Americas

Michelman Inc. Tel: +1 513 793 7766 Fax: +1 513 793 2504

China

Michelman New Material (Shanghai) Co., Ltd. Tel: +86 21 3810 3800 Fax: +86 21 3810 3811

Luxembourg

Michelman International SARL Tel: +352 26 39 44 1 Fax: +352 26 39 44 80

India

Michelman Private Limited Tel: +91 22 6221 3800 Fax: +91 22 6221 3801/02

Singapore

Michelman Asia-Pacific Pte. Ltd. Tel: +65 6861 2822 Fax: +65 6861 2262

The facts stated and the recommendations contained herein are based on our own research and the research of others, and are believed to be accurate. However, no guarantee of their accuracy is made because we cannot cover every possible application for our products nor anticipate every variation encountered in manufacturing equipment and methods. The products discussed are sold without warranty, express or implied and Seller disclaims any warranty of merchantability or fitness for a particular purpose in connection with the purchase of its products. It is recommended that purchasers conduct their own tests to determine the suitability of such products for their particular purpose. Seller shall not be liable for any injury, loss or damage, direct or consequential arising out of the use of or the inability to use the product. Statements concerning the possible use of our products are not intended as recommendations to use our products in the infringement of any patent and our products are sold without warranty of non-infringement.

© 2025 MICHELMAN, INC. All rights reserved. ® Reg. U.S. Pat. TM Off. All marks contained herein are registered or owned by Michelman, Inc. Michelman is ISO 9001:2015 certified