

Michem® Guard 7140

BRAND FAMILY OVERVIEW Michem® Guard waterborne dispersions add optimum slip, and abrasion, mar, and block resistance without using solvents. Some also provide a matting effect for a more natural appearance.

USAGE This water-based dispersion provides block, rub, and abrasion resistance, and matting in pigmented and semi-gloss coatings, inks, and overprint varnishes. It also produces smooth satin finishes at a 5-10% addition rate.

DESCRIPTION Anionic polyethylene dispersion

PERFORMANCE ATTRIBUTES	This product is used in many applications including the following:	
	Market	Properties Imparted
	Building Paints	mar resistance
	Exterior Wood Protection	durability, scratch resistance
	Gloves	matting, rub resistance
	Inks	abrasion resistance, block resistance, mar resistance, matting, rub resistance, scratch resistance
	Leather	abrasion resistance, block resistance, mar resistance, scratch resistance, scuff resistance and feel
	OEM Applied Wood Protection	abrasion resistance, block resistance, matting, scratch resistance
	Overprint Varnishes	abrasion resistance, block resistance, matting, rub resistance, scratch resistance

PHYSICAL PROPERTIES

Appearance:	White liquid
Solids Type:	Polyethylene
Emulsifier Charge:	Anionic
Non-Volatile (%) :	39.5 - 40.5
pH:	5.0 - 7.0
Recommended pH of your system:	4.0 - 10.0
Brookfield Viscosity (cps):	< 500
Spindle Number:	3
RPM:	60

page 1 www.michelman.com



Michem® Guard 7140

(and PRODUCT CODE)

SITE OF MANUFACTURE USA (MGRD7140), Singapore (MGRD7140.S)

STORAGE Keep containers tightly closed in a dry, cool and well-ventilated place. Keep from freezing.

HANDLING Avoid contact with skin, eyes or clothing. Do not eat, drink or smoke when using this product. Handle in accordance with good industrial hygiene and safety practice. Use personal protection equipment.

Revised 09 August 2022

The following information for this product, specific to each site of manufacture, is available upon request:

- Material Safety Data Sheets in various formats and languages (includes global chemical inventory listing)
- Food Contact Declaration of Compliance (if applicable)

Americas

Michelman Inc. Tel: +1 513 793 7766 Fax: +1 513 793 2504

China

Michelman New Material (Shanghai) Co., Ltd. Tel: +86 21 3810 3800 Fax: +86 21 3810 3811

Luxembourg

Michelman International SARL Tel: +352 26 39 44 1 Fax: +352 26 39 44 80

India

Michelman Private Limited Tel: +91 22 6221 3800 Fax: +91 22 6221 3801/02

Singapore

Michelman Asia-Pacific Pte. Ltd. Tel: +65 6861 2822 Fax: +65 6861 2262

The facts stated and the recommendations contained herein are based on our own research and the research of others, and are believed to be accurate. However, no guarantee of their accuracy is made because we cannot cover every possible application for our products nor anticipate every variation encountered in manufacturing equipment and methods. The products discussed are sold without warranty, express or implied and Seller disclaims any warranty of merchantability or fitness for a particular purpose in connection with the purchase of its products. It is recommended that purchasers conduct their own tests to determine the suitability of such products for their particular purpose. Seller shall not be liable for any injury, loss or damage, direct or consequential arising out of the use of or the inability to use the product. Statements concerning the possible use of our products are not intended as recommendations to use our products in the infringement of any patent and our products are sold without warranty of non-infringement.

© 2025 MICHELMAN, INC. All rights reserved. ® Reg. U.S. Pat. TM Off. All marks contained herein are registered or owned by Michelman, Inc. Michelman is ISO 9001:2015 certified.

page 2 www.michelman.com