

Michem® In-Line Primer 030

BRAND FAMILY OVERVIEW Primers explicitly designed for use on HP Indigo equipment with an in-line priming applicator to impart a print-receptive surface to most substrates, and improve the ink transfer and adhesion of HP Indigo ElectroInk.

USAGE Imparts a print-receptive surface to most substrates to improve the ink transfer and adhesion of HP Indigo Electroinks. It is used in the in-line priming unit available as options on both the WS6000 and WS6600 presses. The primer improves the surface of a wide range of paper substrates, both uncoated and clay-coated of various basis weights, as well as PSA label stocks with paper or polyolefin face-stocks, including textured papers and transparent labelstock. This product possesses good stability to light and is resistant to yellowing.

DESCRIPTION Primer for Digital Printing

PHYSICAL PROPERTIES The following properties are typical but should not be considered specifications:

Appearance:	White, translucent liquid
pH:	8.0 - 10.0
Brookfield Viscosity (cps) :	< 100
Spindle Number:	1
RPM:	60
Shelf Life (months) :	The product has a shelf life of 24 months from date of manufacture when storage and handling instructions are followed.

SITE OF MANUFACTURE (and PRODUCT CODE) USA (ILP030), Belgium (ILP030.E), Singapore (ILP030.S)

APPLICATION DATA Michem® In-Line Primer 030 is designed specifically for use in the in-line priming unit of an HP Indigo WS6600 printing press. As such, when run as instructed by HP Indigo on paper substrates, the ILP unit will apply the correct amount of primer to achieve optimal ink adhesion and press performance. EZ Cup Viscosity - #3 Cup, 8 - 13 seconds. Do not dilute.

Revised 11 April 2018

The following information for this product, specific to each site of manufacture, is available upon request:

- Material Safety Data Sheets in various formats and languages (includes global chemical inventory listing)
- Food Contact Declaration of Compliance (if applicable)

Michem® In-Line Primer 030

Americas

Michelman Inc.
Tel: +1 513 793 7766
Fax: +1 513 793 2504

China

Michelman New Material
(Shanghai) Co., Ltd.
Tel: +86 21 2098 6880
Fax: +86 21 3810 3811

India

Michelman Private Limited
(formerly known as
Michelman Chemicals Pvt Ltd)
Tel: +91 22 28672783
Fax: +91 22 28672784

Japan

Michelman Japan LLC
Tel: +81 3 45 80 14 90
Fax: +81 3 45 80 27 01

Luxembourg

Michelman SARL
Tel: +352 26 39 44 1
Fax: +352 26 39 44 80

Singapore

Michelman Asia-Pacific Pte. Ltd.
Tel: +65 6861 2822
Fax: +65 6861 2262

The facts stated and the recommendations contained herein are based on our own research and the research of others, and are believed to be accurate. However, no guarantee of their accuracy is made because we cannot cover every possible application for our products nor anticipate every variation encountered in manufacturing equipment and methods. The products discussed are sold without warranty, express or implied and Seller disclaims any warranty of merchantability or fitness for a particular purpose in connection with the purchase of its products. It is recommended that purchasers conduct their own tests to determine the suitability of such products for their particular purpose. Seller shall not be liable for any injury, loss or damage, direct or consequential arising out of the use of or the inability to use the product. Statements concerning the possible use of our products are not intended as recommendations to use our products in the infringement of any patent and our products are sold without warranty of non-infringement.

© 2021 MICHELMAN, INC. All rights reserved. ® Reg. U.S. Pat. TM Off.
All marks contained herein are registered or owned by Michelman, Inc.
Michelman is ISO 9001:2015 certified.