

Michem® Lube 160 PFP

BRAND FAMILY OVERVIEW Michem® Lube is a versatile family of wax emulsions used to improve processing and performance in many industries, as well as provide a wide array of surface properties.

USAGE This phenol-free additive provides slip and anti-block properties when used in coatings for seeds, metal, wood and OPP films.

DESCRIPTION Anionic carnauba emulsion

PERFORMANCE ATTRIBUTES This product is used in many applications including the following:

Market	Properties Imparted
Automotive Care	<i>APEO free, buffability, gloss enhancement, lubricity, mar resistance</i>
Building Paints	<i>block resistance, lubricity, mar resistance, release, scratch resistance</i>
Can & Coil	<i>lubricity</i>
Exterior Wood Protection	<i>block resistance, lubricity, mar resistance, release, scratch resistance</i>
Functional Coatings	<i>block resistance, buffability, lubricity, mar resistance, release, scratch resistance</i>
Furniture Polish	<i>block resistance, buffability</i>
Interior Furniture & Floor	<i>block resistance, buffability, lubricity, mar resistance, release, scratch resistance</i>
Leather	<i>block resistance, buffability, lubricity, mar resistance, release, scratch resistance</i>
OEM Applied Wood Protection	<i>block resistance, buffability, lubricity, mar resistance, release, scratch resistance</i>
Overprint Varnishes	<i>block resistance, buffability, lubricity, mar resistance, release, scratch resistance</i>

Michem® Lube 160 PFP

PHYSICAL PROPERTIES

The following properties are typical but should not be considered specifications:

Appearance:	Cream colored, opaque liquid
Freeze/Thaw Stability:	Stable after 5 Cycles
Non-Volatile (%) :	24.5 - 25.5
Specific Gravity:	0.99 - 1.01
pH:	4.0 - 7.5
Recommended pH of your system:	1.0 - 12.0
Brookfield Viscosity (cps) :	< 15
Spindle Number:	1
RPM:	60
Shelf Life (months) :	The product has a shelf life of 12 months from date of manufacture when storage and handling instructions are followed.

SITE OF MANUFACTURE (and PRODUCT CODE)

USA (ML160PFP), Belgium (ML160PFP.E), Singapore (ML160PFP.S)

STORAGE

Keep containers tightly closed in a dry, cool and well-ventilated place.

HANDLING

Handle in accordance with good industrial hygiene and safety practice. Use personal protection equipment.

Revised 06 September 2022

The following information for this product, specific to each site of manufacture, is available upon request:

- Material Safety Data Sheets in various formats and languages (includes global chemical inventory listing)
- Food Contact Declaration of Compliance (if applicable)

Michem® Lube 160 PFP

Americas

Michelman Inc.
Tel: +1 513 793 7766
Fax: +1 513 793 2504

Luxembourg

Michelman International SARL
Tel: +352 26 39 44 1
Fax: +352 26 39 44 80

Singapore

Michelman Asia-Pacific Pte. Ltd.
Tel: +65 6861 2822
Fax: +65 6861 2262

China

Michelman New Material
(Shanghai) Co., Ltd.
Tel: +86 21 3810 3800
Fax: +86 21 3810 3811

India

Michelman Private Limited
Tel: +91 22 6221 3800
Fax: +91 22 6221 3801/02

The facts stated and the recommendations contained herein are based on our own research and the research of others, and are believed to be accurate. However, no guarantee of their accuracy is made because we cannot cover every possible application for our products nor anticipate every variation encountered in manufacturing equipment and methods. The products discussed are sold without warranty, express or implied and Seller disclaims any warranty of merchantability or fitness for a particular purpose in connection with the purchase of its products. It is recommended that purchasers conduct their own tests to determine the suitability of such products for their particular purpose. Seller shall not be liable for any injury, loss or damage, direct or consequential arising out of the use of or the inability to use the product. Statements concerning the possible use of our products are not intended as recommendations to use our products in the infringement of any patent and our products are sold without warranty of non-infringement.

© 2026 MICHELMAN, INC. All rights reserved. ® Reg. U.S. Pat. TM Off.
All marks contained herein are registered or owned by Michelman, Inc.
Michelman is ISO 9001:2015 certified.