MICHELMAN

Michem® Lube 160RPH

BRAND FAMILY OVERVIEW	Michem [®] Lube is a versatile family of wax emulsions used to improve processing and performance in many industries, as well as provide a wide array of surface properties.	
USAGE	APEO-free and formaldehyde-free slip additive made from renewable materials allowing to control the coefficient of friction. This additive enters the formulation of acrylics, PVdC and Michelman low temperature heat seal coatings without affecting bond strength, printability and barrier properties of the coatings. Michem [®] Lube 160 RPH fully complies with FDA and EU food contact regulations.	
DESCRIPTION	Carnauba Emulsion	
PERFORMANCE ATTRIBUTES	This product is used in many applications including the following:	
	Market	Properties Imparted
	Functional Coatings	block resistance, lubricity, slip resistance
	Inks	block resistance, chemical resistance, mar resistance, release, rub resistance
PHYSICAL PROPERTIES	The following properties are typical but should not be considered specifications:	
	Appearance:	Cream colored, opaque liquid
	Freeze/Thaw Stability:	Stable
	Non-Volatile (%) :	24.5 - 25.5
	Specific Gravity:	0.99 - 1.01
	pH:	4.0 - 7.5
	Brookfield Viscosity (cps) :	< 15
	Spindle Number:	1
	RPM:	60
	Shelf Life (months) :	The product has a shelf life of 12 months from date of manufacture when storage and handling instructions are followed.
SITE OF MANUFACTURE (and PRODUCT CODE)	USA (ML160RPH), Belgium (ML1	60RPH.E), Singapore (ML160RPH.S)

APPLICATION DATA To be used as additive.

MICHELMAN

Michem® Lube 160RPH

STORAGE Keep containers tightly closed in a dry, cool and well-ventilated place. Keep out of the reach of children. Store locked up.

HANDLING Avoid contact with skin, eyes or clothing. Do not eat, drink or smoke when using this product. Handle in accordance with good industrial hygiene and safety practice.

Revised 04 August 2020

The following information for this product, specific to each site of manufacture, is available upon request:

- Material Safety Data Sheets in various formats and languages (includes global chemical inventory listing)
- Food Contact Declaration of Compliance (if applicable)

Americas

China

Michelman Inc. Tel: +1 513 793 7766 Fax: +1 513 793 2504

Michelman New Material

(Shanghai) Co., Ltd. Tel: +86 21 3810 3800

Fax: +86 21 3810 3811

Michelman International SARL Tel: +352 26 39 44 1 Fax: +352 26 39 44 80

Luxembourg

India

Michelman Private Limited Tel: +91 22 6221 3800 Fax: +91 22 6221 3801/02 Michelman Asia-Pacific Pte. Ltd. Tel: +65 6861 2822 Fax: +65 6861 2262

Singapore

others, and are believed to be accurate. However, no guarantee of their accuracy is made because we cannot cover every possible application for our products nor anticipate every variation encountered in manufacturing equipment and methods. The products discussed are sold without warranty, express or implied and Seller disclaims any warranty of merchantability or fitness for a particular purpose in connection with the purchase of its products. It is recommended that purchasers conduct their own tests to determine the suitability of such products for their particular purpose. Seller shall not be liable for any injury, loss or damage, direct or consequential arising out of the use of or the inability to use the product. Statements concerning the possible use of our products are not intended as recommendations to use our products in the infringement of any patent and our products are sold without warranty of non-infringement.

The facts stated and the recommendations contained herein are based on our own research and the research of

© 2025 MICHELMAN, INC. All rights reserved. ® Reg. U.S. Pat. TM Off. All marks contained herein are registered or owned by Michelman, Inc. Michelman is ISO 9001:2015 certified.