

Michem® Lube 985

BRAND FAMILY OVERVIEW Michem® Lube is a versatile family of nanoscale wax emulsions, which are mostly carnauba and paraffin-based, used to improve processing and performance in many industries, as well as provide a wide array of surface properties.

USAGE Provides slip, release, and anti-blocking properties in several applications, including wood coatings, latex gloves, and floor and auto polishes. It can also be blended with synthetic and natural lattices.

DESCRIPTION Carnauba / Paraffin Wax blend Emulsion

PERFORMANCE ATTRIBUTES This product is used in many applications including the following:

| Market | Properties Imparted |
|----------------------------|--|
| Automotive Care | <i>APEO free, buffability, gloss enhancement, lubricity, mar resistance, water beading, water resistance</i> |
| Exterior Wood Protection | <i>block resistance, release, slip resistance</i> |
| Gloves | <i>block resistance, detackifier, mold release, slip resistance</i> |
| Household | <i>slip resistance</i> |
| Industrial & Institutional | <i>block resistance, release, slip resistance</i> |

PHYSICAL PROPERTIES The following properties are typical but should not be considered specifications:

| | |
|--------------------------------|---|
| Appearance: | White liquid |
| Freeze/Thaw Stability: | None: protect from freezing |
| Non-Volatile (%) : | 39.5 - 40.5 |
| Specific Gravity: | 0.98 - 1.00 |
| pH: | 4.5 - 7.0 |
| Recommended pH of your system: | 1.0 - 12.0 |
| Brookfield Viscosity (cps) : | < 1500 |
| Spindle Number: | 3 |
| RPM: | 60 |
| Shelf Life (months) : | The product has a shelf life of 12 months from date of manufacture when storage and handling instructions are followed. |

SITE OF MANUFACTURE USA (ML985)
(and PRODUCT CODE)

Michem® Lube 985

STORAGE Keep containers tightly closed in a dry, cool and well-ventilated place. Keep from freezing.

HANDLING Avoid contact with eyes, skin and clothing. Handle in accordance with good industrial hygiene and safety practice. Use personal protective equipment as required.

Revised 04 August 2020

The following information for this product, specific to each site of manufacture, is available upon request:

- Material Safety Data Sheets in various formats and languages (includes global chemical inventory listing)
- Food Contact Declaration of Compliance (if applicable)

Americas

Michelman Inc.
Tel: +1 513 793 7766
Fax: +1 513 793 2504

China

Michelman New Material
(Shanghai) Co., Ltd.
Tel: +86 21 2098 6880
Fax: +86 21 3810 3811

India

Michelman Private Limited
(formerly known as
Michelman Chemicals Pvt Ltd)
Tel: +91 22 28672783
Fax: +91 22 28672784

Japan

Michelman Japan LLC
Tel: +81 3 45 80 14 90
Fax: +81 3 45 80 27 01

Luxembourg

Michelman SARL
Tel: +352 26 39 44 1
Fax: +352 26 39 44 80

Singapore

Michelman Asia-Pacific Pte. Ltd.
Tel: +65 6861 2822
Fax: +65 6861 2262

The facts stated and the recommendations contained herein are based on our own research and the research of others, and are believed to be accurate. However, no guarantee of their accuracy is made because we cannot cover every possible application for our products nor anticipate every variation encountered in manufacturing equipment and methods. The products discussed are sold without warranty, express or implied and Seller disclaims any warranty of merchantability or fitness for a particular purpose in connection with the purchase of its products. It is recommended that purchasers conduct their own tests to determine the suitability of such products for their particular purpose. Seller shall not be liable for any injury, loss or damage, direct or consequential arising out of the use of or the inability to use the product. Statements concerning the possible use of our products are not intended as recommendations to use our products in the infringement of any patent and our products are sold without warranty of non-infringement.

© 2021 MICHELMAN, INC. All rights reserved. ® Reg. U.S. Pat. TM Off.
All marks contained herein are registered or owned by Michelman, Inc.
Michelman is ISO 9001:2015 certified.