

VaporCoat® 2200

BRAND FAMILY OVERVIEW VaporCoat® recyclable water-based coatings confer high barrier properties to paper-based packaging and wraps. VaporCoat® hinders water vapor transmission so perishables stay fresh, frozen goods remain intact, and sensitive contents arrive in factory condition. For greater food safety and preservation, select VaporCoat® grades can also inhibit contaminants ordinarily found in recycled paper from migrating into packaged dry food.

USAGE VaporCoat® 2200 is an FDA-compliant, recyclable water based coating for chipboard, SBS, SUS and kraft paper. It can often replace polyethylene packaging films used in many types of food and non-food packaging, including multiwall bags.

DESCRIPTION Low odor, low MVTR, water and grease resistant coating

PERFORMANCE ATTRIBUTES This product is used in many applications including the following:

Market	Properties Imparted
Barrier Coatings	grease & oil resistance, MVTR, water resistance
Functional Coatings	barrier, grease & oil resistance, water resistance

PHYSICAL PROPERTIES The following properties are typical but should not be considered specifications:

Appearance:	Off-white, thin liquid
Solids Type:	Acrylic
Non-Volatile (%) :	38.5 - 39.5
DIN Cup Viscosity (sec) :	14 - 16
DIN Cup Number:	4
pH:	8.2 - 9.2
Brookfield Viscosity (cps) :	100 - 300
Spindle Number:	2
RPM:	60

(and PRODUCT CODE)

SITE OF MANUFACTURE Belgium (VAPCT2200.E), Singapore (VAPCT2200.S)

APPLICATION DATA VaporCoat® 2200 is best applied by rod coater at a rate of 4-7 wet pounds per MSF (19.5-34gsm) and as a pre-applied coating or in-line at the wet end of the corrugator or by blade at the dry end of the corrugator.

> page 1 www.michelman.com



VaporCoat® 2200

STORAGE Keep containers tightly closed in a dry, cool and well-ventilated place. Keep from freezing.

HANDLING Ensure adequate ventilation. Handle in accordance with good industrial hygiene and safety practice. If this product contains synthetic polymer microparticles, ensure that the product is not released to the environment. If applicable, the product should be mixed in closed containers to prevent a release of synthetic polymer microparticles into the environment.. Use personal protective equipment as required.

Revised 24 October 2025

The following information for this product, specific to each site of manufacture, is available upon request:

- Material Safety Data Sheets in various formats and languages (includes global chemical inventory listing)
- Food Contact Declaration of Compliance (if applicable)

Americas

Michelman Inc. Tel: +1 513 793 7766 Fax: +1 513 793 2504

China

Michelman New Material (Shanghai) Co., Ltd. Tel: +86 21 3810 3800 Fax: +86 21 3810 3811

Luxembourg

Michelman International SARL Tel: +352 26 39 44 1 Fax: +352 26 39 44 80

Michelman Private Limited Tel: +91 22 6221 3800 Fax: +91 22 6221 3801/02

Singapore

Michelman Asia-Pacific Pte. Ltd. Tel: +65 6861 2822 Fax: +65 6861 2262

The facts stated and the recommendations contained herein are based on our own research and the research of others, and are believed to be accurate. However, no guarantee of their accuracy is made because we cannot cover every possible application for our products nor anticipate every variation encountered in manufacturing equipment and methods. The products discussed are sold without warranty, express or implied and Seller disclaims any warranty of merchantability or fitness for a particular purpose in connection with the purchase of its products. It is recommended that purchasers conduct their own tests to determine the suitability of such products for their particular purpose. Seller shall not be liable for any injury, loss or damage, direct or consequential arising out of the use of or the inability to use the product. Statements concerning the possible use of our products are not intended as recommendations to use our products in the infringement of any patent and our products are sold without warranty of non-infringement.

© 2025 MICHELMAN, INC. All rights reserved. ® Reg. U.S. Pat. TM Off. All marks contained herein are registered or owned by Michelman, Inc. Michelman is ISO 9001:2015 certified.

page 2 www.michelman.com