

VaporCoat® 2240

BRAND FAMILY OVERVIEW VaporCoat® recyclable water-based coatings confer high barrier properties to paper-based packaging and wraps. VaporCoat® hinders water vapor transmission so perishables stay fresh, frozen goods remain intact, and sensitive contents arrive in factory condition. For greater food safety and preservation, select VaporCoat® grades can also inhibit contaminants ordinarily found in recycled paper from migrating into packaged dry food.

USAGE Paraffin-free, water-resistant, water vapor transmission rate (WVTR), and heat seal coating for various applications.

DESCRIPTION Water resistant WVTR and heat seal coating

PERFORMANCE ATTRIBUTES This product is used in many applications including the following:

Market	Properties Imparted
Barrier Coatings	grease & oil resistance, heat seal, MVTR, water resistance
Food Service	grease & oil resistance, heat seal, MVTR, water resistance, water vapor resistance
Functional Coatings	grease & oil resistance, heat seal, water resistance
Heat Seal Coatings	heat seal, MVTR, Substrate - paper
Perishables	MVTR, water resistance

PHYSICAL PROPERTIES The following properties are typical but should not be considered specifications:

Appearance:	White liquid
Solids Type:	Styrene/Acrylic copolymer
Non-Volatile (%):	40.0 - 43.5
pH:	8.0 - 9.0
Brookfield Viscosity (cps):	50 - 1000
Spindle Number:	3
RPM:	60

SITE OF MANUFACTURE Belgium (VC2240.E)
(and PRODUCT CODE)

APPLICATION DATA Rod/Gravure/Flexo

VaporCoat® 2240

STORAGE Keep containers tightly closed in a dry, cool and well-ventilated place.

HANDLING Avoid contact with skin, eyes or clothing. Do not eat, drink or smoke when using this product. Ensure adequate ventilation. Handle in accordance with good industrial hygiene and safety practice. In case of insufficient ventilation, wear suitable respiratory equipment. Take off contaminated clothing and wash before reuse. Use personal protection equipment.

Revised 16 March 2023

The following information for this product, specific to each site of manufacture, is available upon request:

- Material Safety Data Sheets in various formats and languages (includes global chemical inventory listing)
- Food Contact Declaration of Compliance (if applicable)

Americas

Michelman Inc.
Tel: +1 513 793 7766
Fax: +1 513 793 2504

Luxembourg

Michelman International SARL
Tel: +352 26 39 44 1
Fax: +352 26 39 44 80

Singapore

Michelman Asia-Pacific Pte. Ltd.
Tel: +65 6861 2822
Fax: +65 6861 2262

China

Michelman New Material
(Shanghai) Co., Ltd.
Tel: +86 21 3810 3800
Fax: +86 21 3810 3811

India

Michelman Private Limited
Tel: +91 22 6221 3800
Fax: +91 22 6221 3801/02

The facts stated and the recommendations contained herein are based on our own research and the research of others, and are believed to be accurate. However, no guarantee of their accuracy is made because we cannot cover every possible application for our products nor anticipate every variation encountered in manufacturing equipment and methods. The products discussed are sold without warranty, express or implied and Seller disclaims any warranty of merchantability or fitness for a particular purpose in connection with the purchase of its products. It is recommended that purchasers conduct their own tests to determine the suitability of such products for their particular purpose. Seller shall not be liable for any injury, loss or damage, direct or consequential arising out of the use of or the inability to use the product. Statements concerning the possible use of our products are not intended as recommendations to use our products in the infringement of any patent and our products are sold without warranty of non-infringement.

© 2026 MICHELMAN, INC. All rights reserved. ® Reg. U.S. Pat. TM Off.

All marks contained herein are registered or owned by Michelman, Inc.

Michelman is ISO 9001:2015 certified.